

RapidClean -

Floor & Wall

Directions for use:

Shake container well before use. Use directly from container, do not dilute or mix with any other product. Always carry out a test first to ensure the finished result is acceptable.

Apply in dry weather +5°C and rising, on dry or slightly damp material (remove fungi or moss as much as possible before applying product), using a low-pressure sprayer until the surface is saturated, apply from bottom upwards. Leave 30-90 minutes. Allow for more time in cold weather (less than 10°C).

Best results (outside use) allow product to work for 8 hours whilst no rain fall expected (rinse with water or high pressure washer). For lasting results, we recommend the use of RapidGuard Multi-Surface Protector, see RapidGuard tech data. Clean tools and equipment with water immediately after use.

Uses:

Recommended for the treatment of brick, sandstone, rendered walls, paths, drives, monuments, decking and patios. It is also very efficient in cleaning lime render surfaces.

Coverage:

Values for 1 Litre: 3-5m²

Caution:

Not to be diluted or mixed with another product. Not to be applied to organic, metallic or non-porous surfaces. Not to be applied when likelihood of rain forecast within 12 hours following application or when air or surface temperatures below 5°C. Store product in dry conditions temperatures above 5°C.

Useful Info:

Wear suitable gloves and eye protection. Best results apply between 10-30°C. Do not spread product too far as this may result in poor penetration. Do not apply when temp is below 5°C.

RapidClean

High performance cleaner, removes organic and microbiological soiling from porous façade surfaces.

Natural stone, timber, concrete, brick, terracotta & render.

Treated surfaces can simply be rinsed with water without using a pressure washer.

Health & Safety:

For further product information please consult MSDS document

LRS-Systems

Prees Green

SY13 2BN