

RapidGuard - Multi-Surface Protector

Directions for use:

Try a small test area to ensure the desired results. Shake container well. Surfaces must be clean dry and free from all natural growth, dust, efflorescence salt and contaminants (we recommend a RapidClean product or facade cleaner). Apply product with a brush, roller or low-pressure spray in one application to saturation of the surface, apply from bottom upwards, do not allow to drip. Remove excess product with a dry cloth within 30 minutes. Treated surfaces will be visually dry within 90 minutes' dependent on surface type, surrounding temperature and humidity. Clean all tools and equipment with water immediately after use. Optimum results achieved in 5-7 days, although the system will start performing once dried.

Uses:

Brick, Concrete, Limestone, Granite, Slate, Porcelain, Terracotta, Marble, Sandstone and other porous surfaces. Suitable for highly polished materials and pre-cast concrete panels.

Coverage:

Values for 1 Litre: Limestone 1-4m², Granite 15m², Slate 8-10m², Porcelain 15m², Concrete 6-8m², Terracotta 7m², Marble 13m², Sandstone 6-8m², Brick 5-7m². Interior and exterior use.

Caution:

Not to be diluted or mixed with another product. Not to be applied to organic, metallic or non-porous surfaces. Not to be applied when likelihood of rain forecast within 12 hours following application or when air or surface temperatures below 5°C. Store product in dry conditions temperatures above 5°C.

Specially formulated to repel water, protect the surface and prevent porous surfaces from being stained, without changing the surface colour or appearance

Health & Safety:

For further product information please consult MSDS document

LRS-Systems
Prees Green
SY13 2BN